

IQV Cordless Tools



W360-2L

* All kits contain the tool with 2 Li-Ion batteries and the universal charger.

W360 Tool only

W360-2L Kit*

- 1/2" □
- 19.2 V.
- 488 Nm (360 ft-lb).
- Only 2.82 kg.
- Twin-Cam impact mechanism.



W175 Tool only

W175-2L Kit*

- 1/2" □
- 14.4 V.
- 237 Nm (175 ft-lb).
- Only 2.05 kg.
- Twin-Cam impact mechanism.



W150 Tool only

W150-2L Kit*

- 3/8" □
- 14.4 V.
- 203 Nm (150 ft-lb).
- Only 2.05 kg.
- Twin-Cam impact mechanism.



W040SQ Tool only

W040SQ-2L Kit*

- 3/8" □
- 7.2 V.
- 54 Nm (40 ft-lb).
- Only 1.23 kg and 178 mm.
- Twin-Cam impact mechanism.



W150QC Tool only

W150QC-2L Kit*

- 1/4" □
- 14.4 V.
- 203 Nm (150 ft-lb).
- Only 2.05 kg.
- Twin-Cam impact mechanism.



W040 Tool only

W040-2L Kit*

- 1/4" □
- 7.2 V.
- 54 Nm (40 ft-lb).
- Only 1.23 kg and 178 mm.
- Twin-Cam impact mechanism.



Specifications

	CPN Tool only	CPN Kit*										
				V	Nm	Nm	rpm	1 min.	kg	mm	dB(A)	m/s ² • k ⁽¹⁾
W360	17003674	17016155	1/2" □	19.2	34-380	488	1 650	2 200	2.82	228	92.3	16.7 • 2.9
W175	45507894	17016072	1/2" □	14.4	34-176	237	2 200	3 000	2.05	208	90.0	11.8 • 3.0
W150	80226970	17006859	3/8" □	14.4	34-176	203	2 200	3 000	2.05	208	91.0	11.8 • 3.0
W040SQ	45505708	17016155	3/8" □	7.2	2-40	54	2 200	2 500	1.23	178	84.0	4.6 • 0.9
W150QC	45507621	17016197	1/4" □	14.4	34-176	203	2 200	3 000	2.05	208	91.0	11.8 • 3.0
W040	17003658	17004656	1/4" □	7.2	2-40	54	2 200	2 500	1.20	178	84.0	4.6 • 0.9

(1) ISO28927 – 3-axis measurement: vibration level • measurement uncertainty.

IQV Cordless Tools

R385 1/2" □ – Tool only

R385-2L 1/2" □ – Kit*

R380 3/8" □ – Tool only

R380-2L 3/8" □ – Kit*

- 14.4 V.
- 94 Nm (70 ft-lb) – 225 rpm.



R145 3/8" □ – Tool only

R145-2L 3/8" □ – Kit*

R140 1/4" □ – Tool only

R140-2L 1/4" □ – Kit*

- 7.2 V.
- 34 Nm (25 ft-lb) – 225 rpm.



Specifications

	CPN Tool only	CPN Kit*									
				V	Nm	Max. Nm	1 min. rpm	kg	mm	dB(A)	m/s ² • k ⁽¹⁾
R385	45498839	17016239	1/2" □	14.4	14-81	94	225	1.90	315	80.8	4.9 • 0.9
R380	45498821	17016338	3/8" □	14.4	14-81	94	225	1.90	315	80.8	4.9 • 0.9
R145	45498854	17016312	3/8" □	7.2	7-34	34	225	1.30	272	74.9	1.4 • 0.6
R140	45498847	17016270	1/4" □	7.2	7-34	34	225	1.30	272	74.9	1.4 • 0.6

(1) ISO28927 – 3-axis measurement: vibration level / measurement uncertainty.

D650
Tool only

D650-2L Kit*

- 19.2 V.
- Keyless chuck: 13 mm (1/2").
- 2 speeds: 0–360 or 0–1 300 rpm.
- 73 Nm (54 ft-lb).
- 17-position clutch.



D550
Tool only

D550-2L Kit*

- 14.4 V.
- Keyless chuck: 13 mm (1/2").
- 2 speeds: 0–360 or 0–1 300 rpm.
- 62 Nm (46 ft-lb).
- 17-position clutch.



D040
Tool only

D040-2L Kit*

- 7.2 V.
- Standard chuck: 6 mm (1/4").
- 0–1 100 rpm.
- 4.5 Nm (3.3 ft-lb).
- Only 1.15 kg and 176 mm.



GC25
Tool only

GC25-2L Kit*

- 14.4 V.
- Ø 75 mm (3 in.).
- 0.25 kW (0.33 hp).
- 25 000 rpm.



GS25
Tool only

GS25-2L Kit*

- 14.4 V.
- 0.25 kW (0.33 hp).
- 27 500 rpm.
- Contains: 1/4" and 6 mm collets.



GR25
Tool only

GR25-2L Kit*

- 14.4 V.
- 0.25 kW (0.33 hp).
- 20 000 rpm.
- Contains: 1/4" and 6 mm collets.



Specifications

	CPN Tool only	CPN Kit*										
				mm	V	Nm	kW	rpm	kg	mm	dB(A)	m/s ² • k ⁽¹⁾
D650	80227002	17004607	13 mm	–	19.2	73	–	360 / 1 300	2.10	244	76.0	2.2 • 0.6
D550	80227051	17004565	13 mm	–	14.4	62	–	360 / 1 300	2.05	244	71.0	2.2 • 0.6
D040	45518230	24930257	6 mm	–	7.2	4.5	–	1 100	1.15	176	63.0	2.4 • 0.9
GC25	45521895	17022872	–	75	14.4	–	0.25	25 000	1.45	242	72.5	6.0 • 1.5
GS25	80236623	17022492	6mm+1/4"	–	14.4	–	0.25	27 500	1.50	240	70.4	2.8 • 0.8
GR25	80236631	17022450	6mm+1/4"	–	14.4	–	0.25	20 000	1.27	230	72.5	4.6 • 1.7

(1) ISO28927 – 3-axis measurement: vibration level • measurement uncertainty.