



Torque Controlled Screwdrivers



Inline Models



Pistol Models

Model	Torque Range		RPM	Type	Air Hose		Avg Air Consumption		Approx Wt(less bit)		Approx Length		Approx Center to Outside		Noise Level db(A)
	In Lbs	NM			In	mm	ft3/min	m3/min	Lb	Kg	In	mm	In	mm	
PTCS-2330-11B	9.7-18.5	1.1-2.1	1100	Inline	1/4	6.35	7	0.2	0.94	0.43	7.36	187	0.61	15.5	70
PTCS-2330-17B	6.2-13.2	.7-1.5	1700	Inline	1/4	6.35	7	0.2	0.94	0.43	7.36	187	0.61	15.5	70
PTCS-2330-23B	3.5-8.8	.4-1	2300	Inline	1/4	6.35	7	0.2	0.94	0.43	7.36	187	0.61	15.5	71
PTCS-2440-08B	14.1-35.2	1.6-4	800	Inline	1/4	6.35	10.5	0.3	1.43	0.65	8.23	209	0.64	16.5	70
PTCS-2440-15B	6.2-19.4	1-2.2	1500	Inline	1/4	6.35	10.5	0.3	1.43	0.65	8.23	209	0.64	16.5	70
PTCS-2440-21B	9.7-23	1-1.7	2100	Inline	1/4	6.35	10.5	0.3	1.43	0.65	8.23	209	0.64	16.5	74
PTCS-2550-05B	44-92.4	5-10.5	500	Inline	3/8	9.50	17.5	0.5	2.2	1	9.45	240	0.77	19.5	74
PTCS-2550-08B	26.4-48.4	3-5.5	800	Inline	3/8	9.50	17.5	0.5	2.2	1	9.45	240	0.77	19.5	75
PTCS-2550-17B	9.7-23	1.5-2.6	1700	Inline	3/8	9.50	17.5	0.5	2.2	1	9.45	240	0.77	19.5	75
PTCS-2550-05PB	44-92.4	5-10.5	500	Pistol	3/8	9.50	17.5	0.5	2.64	1.2	8.55	198	0.77	20	74
PTCS-2550-08PB	26.4-48.4	3-5.5	800	Pistol	3/8	9.50	17.5	0.5	2.64	1.2	8.55	198	0.77	20	75
PTCS-2550-17PB	13.2-22.9	1.5-2.6	1700	Pistol	3/8	9.50	17.5	0.5	2.64	1.2	8.55	198	0.77	20	75

- Long lasting clutch design – 2,000,000 cycle tested
- Accurate Torque Delivery
- Great power to weight for best Ergonomics

- Quick Shut Off Clutch
- Simple Torque Adjustment