

Accessories for air tools

Our delivery program is completed with an extended range of accessories for air tools. In this chapter you will find:

(Spring)balancers

In order to support the weight of pneumatic, hydraulic and electric tools, the use of a spring balancer should be considered. The performance of the tools will be speeded up due to good balance and reduced operator fatigue, when using a spring balancer.

Applications:

- When heavy tools/machines have to be portable.
- Fitting of centre lathe chuck.
- Transportation of parts in a production line.

The models ETP, ETL, ELB and TW from TW-9 upwards have a safety mechanism which starts working in case of spring breakage.

Polyurethane air hoses

No kinks after bending!

The hose stretches easily and retracts automatically. This increases productivity and safety.

Kombi-Kit

The combi-kit is a tool carrier complete with SMC filter/regulator/lubricator unit 3/8" type AC30-F03E + pressure gauge.

Lubricating oil

Yokota NO32 oil is especially developed for the lubrication of air tool systems.

The oil increases the life span of your air tools considerable.

Regulators

Suitable to control the airflow directly at the air-connection of the tool.

(Spring)balancers

Standard model

Type	Brand	Capacity kg	Cable length m	Weight kg	Hose diameter mm	Air cons. l/min	Inlet-thread
RRI-9001/1	RRI	0,5 - 1,5	2,0	0,5	-	-	-
RRI-9003/1	RRI	1,0 - 3,0	2,0	0,7	-	-	-
RRI-9005/1	RRI	2,5 - 5,0	2,0	0,9	-	-	-
EK-00	RRI	0,5 - 1,5	0,5	0,2	-	-	-
EK-0	RRI	0,5 - 1,5	1,0	0,5	-	-	-
TW-3	RRI	1,0 - 3,0	1,3	1,4	-	-	-
TW-5	RRI	2,5 - 5,0	1,3	1,5	-	-	-
TW-9	RRI	4,5 - 9,0	1,3	3,4	-	-	-
TW-15	RRI	9 - 15	1,3	3,8	-	-	-
TW-22	RRI	15 - 22	1,5	7,2	-	-	-
TW-30	RRI	22 - 30	1,5	7,6	-	-	-
TW-40	RRI	30 - 40	1,5	9,8	-	-	-
TW-50	RRI	40 - 50	1,5	10,4	-	-	-
TW-60	RRI	50 - 60	1,5	11,6	-	-	-
TW-70	RRI	60 - 70	1,5	11,8	-	-	-
ETP-14	RRI	120 - 140	1,2	24,1	-	-	-
ETP-15	RRI	140 - 170	1,2	28,7	-	-	-
ETP-16	RRI	170 - 200	1,2	29,7	-	-	-



RRI-9001/1
RRI-9003/1 RRI-9005/1



EK-00 / EK-0



TW3 / TW-5



TW9 t/m TW-70

Hosereel with integrated cable

HTB-0	RRI	0,5 - 1,5	1,3	1,58	6,5	700	PT 1/4"
HTB-1	RRI	1,5 - 3,0	1,3	1,66	6,5	700	PT 1/4"
HTB-2	RRI	3,0 - 5,0	1,3	1,73	6,5	700	PT 1/4"



HTB-0 / HTB-1 / HTB-2



ELF-3 / ELF-5 ELF-9

Long stroke

Type	Brand	Capacity kg	Cable length m	Weight kg
ELF-3	RRI	1,5 - 3,0	2,5	4,1
ELF-5	RRI	3 - 5,0	2,5	4,2
ELF-9	RRI	5 - 9	2,5	4,7
ELF-15	RRI	9 - 15	2,5	10,0
ELF-22	RRI	15 - 22	2,5	10,2
ELB-30 (ELF-30)	RRI	22 - 30	2,5	11,0
ELB-40 (ELF-40)	RRI	30 - 40	2,5	14,0
ELF-50	RRI	40 - 50	2,5	14,5
ELF-60	RRI	50 - 60	2,5	17,0
ELF-70	RRI	60 - 70	2,5	18,0

Ratchet mechanism

RSB-15	RRI	9 - 15	1,5	7,4
RSB-22	RRI	15 - 22	1,5	7,7
RSB-30	RRI	22 - 30	1,5	8,1
RSB-40	RRI	30 - 40	1,5	8,5

Extra safety

The models ETP, ETL, ELB and TW from TW-9 upwards have a safety mechanism which starts working in case of spring.



ELB-serie



RSB-serie