

EKF Series








Deburring and chamfering machine. For quick and precise edge processing

The advantages of the EKF series

- > Straightforward – easy handling, low weight
- > Variable – 3 milling cutters optionally 45°, 30°, or R 2.5 mm
- > Powerful – 1.5 kW motor



SPECIFICATION

	Motor output:	1,500 Watt
	Voltage:	220 - 240 V AC, 50-60 Hz
	Speed range 1:	6,000 min ⁻¹
	Feed:	manually
	Milling cutter optional	
	Chamfer angle and width:	45° – 0 - 6 mm continuously
	Chamfer angle and width:	30° – 0 - 5 mm continuously
	Radius:	R 2.5 mm
	Carbide reversing cutter plates:	3 pcs. per cutter
	Weight:	4.6 kg

ACCESSORIES

ORDER NO.

Milling cutters

ZFR 300.3 – 30°

ZFR 450.3 – 45°

ZFR 452.3 – R 2,5

Sintered carbide reversible disks


SHM 200

SHM 200-E


SHM 202

Base for the processing of small parts

ZKF 100




Changeable carb. reversing plates




Fine adjustment



ZKF 100 – Base for the processing of small parts



Cutting angle and radius



Processing of radii and edges

ORDER NO.

EKF 300.3 / 230 Volt

EKF 300.3 / 110 Volt

EKF 450.3 / 230 Volt

EKF 450.3 / 110 Volt

EKF 452.3 / 230 Volt

EKF 452.3 / 110 Volt

Technical drawing Page 36-37

SCOPE OF DELIVERY

1 Deburring and chamfering machine

1 Milling cutter

3 Sintered carbide reversible disks

1 Jaw spanner WS 22

1 Carry case

1 Sickle spanner

1 Torx screwdriver T9

1 Operating manual

SKF 25










Good work planning, good results with the universal bevel edge milling machine with integrated tube attachment



The advantages of the SKF 25

- > Wide chamfers – up to 15 mm
- > Continuous angle adjustment – from 15 to 60°
- > Handy – with ergonomic handle arrangement
- > Easily guided – with guide rollers

SPECIFICATION

	Motor output:	1.1 kW
	Voltage:	220-240 V AC, 50-60 Hz
	Feed:	manually
	Speed range 1:	2,850 min ⁻¹
	Chamfer width:	15 mm
	Angle adjustment:	15 – 60° continuously
	Safety:	automatic overload cutout / restart lockout
	Weight:	22 kg
	Tools:	Arbor milling cutter, double-row, with 10 sintered carbide reversible disks

ACCESSORIES

ORDER NO.

Arbor milling cutter


ZFR 250*

Sintered carbide reversible disks


SHM 800

*Sintered carbide reversible disks are not included in the delivery.


1 Set = 10 Reversible disks SHM 800




Arbor milling cutter




Wide guide rollers



With integrated tube attachment



... for tube processing



Angle adjustment 15 - 60°

ORDER NO.

SKF 25 / 230 Volt

SKF 25 / 110 Volt

SCOPE OF DELIVERY

1 Bevel edge milling machine

1 Carry case

10 Sintered carbide reversible disks
SHM 800

1 Offset screwdriver

1 Operating manual