

Air drills

- Straight, pistol and angle models
- Drilling capacity: from 1 to 20 mm Ø



Air drills

Fiam air drills: drilling operations on any kind of material with handiness and efficacy

The main technological parameters in drilling operations are the cutting speed and the force with which the drill is moved forwards, both of which are in their turn connected with the type of material being drilled, the diameter of the hole and the idle speed of the drill. Fiam air drills offer considerable advantages, combining high performance with an **excellent** power to weight ratio and design features that make them particularly easy-to-handle in every production field. The range includes various models with straight and pistol grip, or angle drills suitable to drill from 1 to 20 mm diameter; equipped with different kinds of chucks to fix the bits (self-locking chucks and keyed chucks), and models with collet chucks. As regards the type of grip, Fiam air drills are characterized by advanced ergonomic solutions that allow different grip position to suit every work situation thanks to rounded shapes, without sharp edges.

Straight grip drills

There are available the FZ series, extremely compact, the FS and FY series. The capacities of the chucks supplied with the tool vary from 0 to 10 mm and the speeds from 500 to 20.000 r.p.m.

An important benefit is that they can be started at low speed, using a lever, to facilitate initial insertion of the bit. Straight grip drills are ideal for vertical drilling operations.

Pistol grip drills

The FSE, FDE and FY series are the most used for their practicality, handiness and lightness in relation to their performances. The capacities of the chucks supplied with the tool vary from 0 to 13 mm and the speeds from 450 to 20.000 r.p.m.

Pistol grip drills are ideal for horizontal work; their ergonomic shape is ideal to guide the bit with precision and safety and to avoid harmful strain of the wrist.

The pistol grip is better for holes larger than 6-8 mm because it permits the best advancing force.

Twin grip drills

Suitable for holes with a diameter of over 10-13 mm. FO air drills can also be used for boring and tightening.

Angle drills

They are necessary when one needs to drill in tight spaces where access is difficult, such as up against walls, close to metal sections and profiled beams. Models are available with 30° (FZ series) and 90° angle heads. The wide range is available with self docking chuck, with keyed chuck and without chuck; 90° angle drills (FS series) are also available in the version which permits the use of collet instead of the normal keyed chuck. With these models it is possible to have even more reduced head dimensions, especially when used with shorter drill bits. Speeds vary from 500 to 4.500 r.p.m.

Drills-Screwdrivers

All Fiam air drills can be used as screwdrivers; it is sufficient to change the chuck to obtain a screwdriver (without clutch) practical, light and easy to handle.

Special and multi spindle drills

Fiam designs and manufactures special drills to meet the specific needs of individual customers.

Fiam Technical Consultancy Service is at your disposal for further details.



Don't be satisfied with the maximum

Reliability

Productivity

Long lifetime of the components thanks to careful design and quality of the production process which results in less maintenance and repair costs

Great use effectiveness thanks to innovative design systems

The internal gears guarantee constant performance and long lifetime of the tool

The air motors employed ensure high power and maximum output in every production field

Tools are manufactured with high quality materials that guarantee greater resistance to wear

The possibility of using unlubricated compressed air (except FO drills) permits to eliminate lubrication plant costs and to use these tools for high precision tasks (for example electronics, precision mechanics)

Fiam drills guarantee a great versatility of use: they can be used on any kind of material making them the perfect answer to every work situation

Models with 30° and 90° angle heads are ideal in tight spaces where access is difficult, such as up against walls, close to metal sections and profiled beams

All straight air drills can be used as screwdrivers; it is sufficient to change the chuck to obtain a practical, light and handy air screwdriver (without clutch) (see Accessories available upon request on page 18)

Fiam proposes a wide range of air drills with self-locking chuck, with keyed-chuck, without chuck and with collet to solve every application need

All air drills can be started at low speed to facilitate initial insertion of the bit and therefore to obtain faster FO series is particularly effective for heavy-duty drilling and boring operations in which the drill needs to be moved forward with considerable

In special manual drilling situations and drilling-equipment mounted applications, Fiam manufactures special drills, in a very wide range of speeds, with direct air inlet for remote control use, and with smooth or flanged housings





FZ31/90P



Straight air drills FZ, FS, FY

Straight air drills

IDLE SPEED:

from 500 to 20.000 r.p.m.

DRILLING CAPACITY:

from 1 to 10 mm Ø

TYPE OF DRILL:

- with self-locking chuck
- with keyed chuck
- without chuck



STARTING SYSTEM:

lever

APPLICATION FIELD:

they are mainly used in vertical drilling operations on any kind of material



Straight air drills FZ, FS, FY

1100 00 00.01		Qu.	100 of 10	Chuck Capacity	dels maling (e)	, /2000s 9/p	Sienting system	usion tuojan	Ojnenséns (mn)	air On See	Noise level	Vibrailons (ever)ons
Model	Code	Туре	Туре	mm	Туре	r.p.m.	Туре	Kg	ØxL	l/s	dBA	m/s²
FZ45A	122309009	↓	Self-locking chuck	0÷4	_	4500	1	0,480	32×185	6	76	< 2,5
FZ45C	122311145	l l	Keyed chuck	0÷4	-	4500	1	0,430	32×178	6	76	< 2,5
FZ45	122309007		Without chuck	0 : 4*	1	4500	1	0,350	32x153	6	76	< 2,5
FS200C	124611120	↓	Keyed chuck	0÷6	-	20000	1	0,625	40×190	9	76	< 2,5
FS65A	124609043	Į Į	Self-locking chuck	0÷8	-	6500	1	0,840	40×205	9	76	< 2,5
FS65C	124611104	↓	Keyed chuck	0÷8	-	6500	1	0,700	40×190	9	76	< 2,5
FS65	124609014	ļ	Without chuck	0÷8*	2	6500	1	0,570	40x157	9	76	< 2,5
FS48A	124609044	ļ	Self-locking chuck	0÷8	-	5400	1	0,840	40x205	9	76	< 2,5
FS48C	124611106	ļ	Keyed chuck	0÷8	-	5400	1	0,700	40×190	9	76	< 2,5
FS48	124609015	. ↓	Without chuck	0÷8*	2	5400	1	0,570	40x157	9	76	< 2,5
FS33A	124609045	1	Self-locking chuck	0÷8	-	3800	1	0,840	40x205	9	76	< 2,5
FS33C	124611108	. ↓	Keyed chuck	0÷8	-	3800	1	0,700	40×190	9	76	< 2,5
FS33	124609003	1	Without chuck	0÷8*	2	3800	1	0,570	40x157	9	76	< 2,5
FS26A	124609037	Į.	Self-locking chuck	0÷8	-	2900	1	0,840	40x205	9	76	< 2,5
FS26C	124611110	1	Keyed chuck	0÷8	-	2900	1	0,700	40×190	9	76	< 2,5
FS26	124609002	-	Without chuck	0÷8*	2	2900	1	0,570	40x157	9	76	< 2,5
FS17A	124609010	1	Self-locking chuck	1÷10	-	1700	1	1,090	40x255	9	76	< 2,5
FS17C	124611112	Į.	Keyed chuck	1÷10	-	1700	1	0,960	40x235	9	76	< 2,5
FS17	124609054	1	Without chuck	1÷10*	2	1700	1	0,735	40×197	9	76	< 2,5
FS10A	124609046	ļ	Self-locking chuck	1÷10	-	1000	1	1,090	40x255	9	76	< 2,5
FS10C	124611114	1	Keyed chuck	1÷10	-	1000	1	0,960	40x235	9	76	< 2,5
FS10	124609001	-	Without chuck	1÷10*	2	1000	1	0,735	40×197	9	76	< 2,5
FS5A	124609047	Į.	Self-locking chuck	1÷10	-	500	1	1,090	40×255	9	76	< 2,5
FS5C	124611116		Keyed chuck	1÷10	-	500	1	0,960	40×235	9	76	< 2,5
FS5	124609055		Without chuck	1÷10*	2	500	1	0,735	40×197	9	76	< 2,5
FY8A	126311118	Į.	Self-locking chuck	1÷10	-	2600	1	1,330	46×270	11	77	< 2,5
FY8C	126309024	ļ	Keyed chuck	1÷10	-	2600	1	1,195	46×250	11	77	< 2,5
FY8	126309026	į	Without chuck	1÷10*	3	2600	1	0,970	46x213	11	77	< 2,5
FY10A	126311110	ļ	Self-locking chuck	1÷10	_	1800	1	1,330	46x270	11	77	< 2,5
FY10C	126309078	I	Keyed chuck	1÷10	-	1800	1	1,195	46x250	11	77	< 2,5
FY10	126309023	ļ	Without chuck	1÷10*	3	1800	1	0,970	46x213	11	77	< 2,5

Legend

FZ, FS, FY...A = models with self-locking chuck • FZ, FS, FY...C = models with keyed chuck • FZ, FS, FY... = models without chuck. For the right choice, see page 3.

1 - Tapered J 0. • 2 - Threaded 3/8" x 24 UNF. • 3 - Threaded 1/2" x 20 UNF.

* Chuck capacity

The indicated capacity is the maximum recommended.

Legend

- To choose the right air drill, it is necessary to check
- the drilling capacity in the chart on page 3.
 The figures shown are measured at a pressure of 6,3 bar (ISO 2787), the recommended operating pressure.
 Noise level has been measured in accordance with ISO 3744 and ISO 15744.
- Vibrations level has been measured in accordance with ISO 8662
- The code number must be used when ordering.

The models highlighted in black are usually available from stock.

The data given in the table are indicative and can be changed without prior notice. The values indicated for noise levels were obtained in the laboratory, performing tests that comply with the standards stated, but alone are not sufficient for calculating risks. Values measured in the single work places may be higher than those stated. The values of actual exposure and consequent risks are specific and depend on the operator's method of work, the type of work piece and the work place, as well as the operator's time of exposure and his physical conditions.

Fiam cannot be held responsible for any consequences deriving from the use of the information in the table when evaluating risks in the work place over which Fiam has no control. For all further details, please apply to the FiamTechnical Consultancy Service.

Standard equipment (supplied with the tool)

- Drills with self-locking chuck: self-locking chuck Drills with keyed chuck: keyed chuck and key
- Hanging ring

Lever

- Auxiliary grip (except FZ... models) -prEN792 1-12 standard (see page 22)
- Use and maintenance manual
- Eco-friendly packaging

Accessories available upon request

• Wide range of accessories for air drills and the compressed air system (see page 18-23).

Models available upon request

- Models with 0.5 to 5 mm collet chuck (FZ... series)
- Models with 0.5 to 7 mm collet chuck (FS... series)
- Models with 0.5 to 10 mm collet chuck (FY... series)
- In special manual drilling situations and drilling-equipment mounted applications, Fiam manufactures special drills, in a very wide range of speeds, with direct air inlet for remote control use, and with smooth or flanged housings. Given the wide variety of solutions possible, Fiam's qualified Technical Consultancy Service is at your disposal for any further information

Other technical features

/	/ /		/ Supply hoses recommended*			
Models	Air inlet	Recommended hose bore	Rubber	Spiral		
FZ	1/8" gas	Ø 5 mm	693511020	-		
FS, FY	1/4" gas	Ø8mm	693511022	693011020		

^{*} For features of hoses see p. 20

Pistol air drills FSE, FDE, FY, FO

Pistol air drills

IDLE SPEED:

from 170 to 20.000 r.p.m.

DRILLING CAPACITY:

from 1 to 13 mm Ø

TYPE OF DRILL:

- with self-locking chuck
- with keyed chuck
- without chuck



STARTING SYSTEM:

push button

APPLICATION FIELD:

they are suitable for a lot of drilling operations on every type of material and in every industrial field. FO series is particularly effective for **heavy-duty drilling** and boring operations in which the drill needs to be moved forward with considerable force.



Pistol air drills FSE, FDE, FY, FO

<u> </u>		/	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Nicoec	/**************************************	. /		ur /	s (mm)	/88	monion / se	/s
Tros of or		gino.	1700 of 011.04 84001604	Chuck capacity	Output shaft	,	Soming Syster	Weight	Dinensièns (mm)	on messed in	Moise level	Viorazions everzions
Model	Code	Туре	Туре	mm	Туре	r.p.m.	Туре	Kg	ØxLxH	l/s	dBA	m/s²
FSE200PC	124611530	—	Keyed chuck	0÷6	-	20000	7	0,730	38x180x155	9	77	< 2,5
FSE65PA	124611541	7	Self-locking chuck	0÷8	-	6500	7	0,940	38x196x155	9	77	< 2,5
FSE65PC	124611531	7	Keyed chuck	0÷8	-	6500	7	0,800	38x180x155	9	77	< 2,5
FSE65P	124610531	7	Without chuck	0÷8*	1	6500	7	0,670	38x150x155	9	77	< 2,5
FSE48PA	124611542	7	Self-locking chuck	0÷8	-	5400	7	0,940	38x196x155	9	77	< 2,5
FSE48PC	124611532	7	Keyed chuck	0÷8	-	5400	7	0,800	38x180x155	9	77	< 2,5
FSE48P	124610532	7	Without chuck	0÷8*	1	5400	7	0,670	38x150x155	9	77	< 2,5
FSE33PA	124611543	7	Self-locking chuck	0÷8	-	3800	7	0,940	38x196x155	9	77	< 2,5
FSE33PC	124611533	7	Keyed chuck	0÷8	-	3800	7	0,800	38x180x155	9	77	< 2,5
FSE33P	124610533	7	Without chuck	0÷8*	1	3800	7	0,670	38x150x155	9	77	< 2,5
FSE26PA	124611544	7	Self-locking chuck	0÷8	-	2900	7	0,940	38x196x155	9	77	< 2,5
FSE26PC	124611534	7	Keyed chuck	0÷8	-	2900	7	0,800	38x180x155	9	77	< 2,5
FSE26P	124610534	7	Without chuck	0÷8*	1	2900	7	0,670	38x150x155	9	77	< 2,5
FSE17PA	124611545	7	Self-locking chuck	1÷10	-	1700	7	1,180	38x233x155	9	77	< 2,5
FSE17PC	124611535	7	Keyed chuck	1÷10	-	1700	7	1,045	38x210x155	9	77	< 2,5
FSE17P	124610535	~	Without chuck	1÷10*	1	1700	7	0,820	38x175x155	9	77	< 2,5
FSE10PA	124611546	7	Self-locking chuck	1÷10	-	1000	7	1,180	38x233x155	9	77	< 2,5
FSE10PC	124611536	7	Keyed chuck	1÷10	-	1000	7	1,045	38x210x155	9	77	< 2,5
FSE10P	124610536	7	Without chuck	1÷10*	1	1000	7	0,820	38x175x155	9	77	< 2,5
FSE5PA	124611547	7	Self-locking chuck	1÷10	-	500	7	1,180	38x233x155	9	77	< 2,5
FSE5PC	124611537	7	Keyed chuck	1÷10	-	500	7	1,045	38x210x155	9	77	< 2,5
FSE5P	124610537	7	Without chuck	1÷10*	1	500	7	0,820	38x175x155	9	77	< 2,5
FDE60PA	124611550	7	Self-locking chuck	1÷10	-	6000	7	1,080	38x223x155	10	77	< 2,5
FDE60PC	124611560	7	Keyed chuck	1÷10	-	6000	7	0,945	38x200x155	10	77	< 2,5
FDE60P	124610550	7	Without chuck	1÷10*	1	6000	7	0,720	38x165x155	10	77	< 2,5
FDE49PA	124611551	7	Self-locking chuck	1÷10	-	4900	7	1,080	38x223x155	10	77	< 2,5
FDE49PC	124611561	7	Keyed chuck	1÷10	-	4900	7	0,945	38x200x155	10	77	< 2,5
FDE49P	124610551	7	Without chuck	1÷10*	1	4900		0,720	38x165x155	10	77	< 2,5
FDE33PA	124611552	7	Self-locking chuck	1÷10	-	3300	7	1,080	38x223x155	10	77	< 2,5
FDE33PC	124611562	7	Keyed chuck	1÷10	-	3300	7	0,945	38x200x155	10	77	< 2,5
FDE33P	124610552	7	Without chuck	1÷10*	1	3300	7	0,720	38x165x155	10	77	< 2,5
FDE26PA	124611553	7	Self-locking chuck	1÷10	-	2600	7	1,080	38x223x155	10	77	< 2,5
FDE26PC	124611563	7	Keyed chuck	1÷10	-	2600	7	0,945	38x200x155	10	77	< 2,5
FDE26P	124610553	7	Without chuck	1÷10*	1	2600	7	0,720	38x165x155	10	77	< 2,5
FY6PA	126311556	7	Self-locking chuck	1÷10	-	3200	7	1,540	46x222x170	11	77	< 2,5
FY6PC	126309103	7	Keyed chuck	1÷10	-	3200	7	1,400	46x200x170	11	77	< 2,5
FY6P	126309036	7	Without chuck	1÷10*	2	3200	7	1,180	46×165×170	11	77	< 2,5

1700 ord		Onio Onio	Tro or on or supplied	chuck capacity	(a)	. / 2000/50/10/	Sienting system	Weight The	Oinensions (mm)	Compressed in	Noise level	VID 22:078 61/9 2078
Model	Code	Туре	Туре	mm	Туре	r.p.m.	Туре	Kg	ØxLxH	l/s	dBA	m/s²
FY8PA	126311558	7	Self-locking chuck	1÷10	-	2600		1,540	46x222x170	11	76	< 2,5
FY8PC	126309019	7	Keyed chuck	1÷10	-	2600	7	1,400	46x200x170	11	76	< 2,5
FY8P	126309020	7	Without chuck	1÷10*	2	2600	7	1,180	46x165x170	11	76	< 2,5
FY10PA	126311560	7	Self-locking chuck	1÷10	-	1800	7	1,540	46x222x170	11	76	< 2,5
FY10PC	126309015	7	Keyed chuck	1÷10	-	1800	7	1,400	46x200x170	11	76	< 2,5
FY10P	126309018	7	Without chuck	1÷10*	2	1800	7	1,180	46x165x170	11	76	< 2,5
FY13PA	126311563	7	Self-locking chuck	1÷13	-	750	7	2,000	46x263x170	11	76	< 2,5
FY13PC	126309007	7	Keyed chuck	1÷13	-	750	7	1,845	46x238x170	11	76	< 2,5
FY13P	126309021	7	Without chuck	1÷13*	2	750	7	1,485	46x195x170	11	76	< 2,5
FY14PA	126311564	7	Self-locking chuck	1÷13	-	450	7	2,000	46x263x170	11	76	< 2,5
FY14PC	126309030	7	Keyed chuck	1÷13	-	450	7	1,845	46x238x170	11	76	< 2,5
FY14P	126309035	7	Without chuck	1÷13*	2	450	7	1,485	46x195x170	11	76	< 2,5
FO12P	127011512	-4	Without chuck	-	3	2000	-+	3,050	65x200x360	14	91	< 2,5
FO16P	127011516	-+	Without chuck	-	3	950	-+	3,600	65x236x360	14	91	< 2,5
FO20P	127011520	-4	Without chuck	-	3	600	-+	3,600	65x236x360	14	91	< 2,5
FO3P	127011530	-+	Without chuck	-	3	170	-+	4,180	65x272x360	14	91	< 2,5

Legend

FSE, FDE, FY, ...PA = models with self-locking chuck • FSE, FDE, FY, ...PC = models with keyed chuck • FSE, FDE, FY, FO...P = models without chuck • For the right choice, see page 3.

Legend Nush button Push button

(a) OUTPUT SHAFT

1 - Threaded 3/8" x 24 UNF • 2 - Threaded 1/2" x 20 UNF • 3 - Tapered n. 2

* Chuck capacity The indicated capacity is the maximum recommended.

• To choose the right air drill, it is necessary to check To close the right air dmin, its interessary to check the drilling capacity in the chart on page 3. The figures shown are measured at a pressure of 6,3 bar (ISO 2787), the recommended operating pressure. Noise level has been measured in accordance with ISO 3744 and ISO 15744. *Ubrations level has been measured in accordance with ISO 8662 standard.

- The code number must be used when ordering.

The models highlighted in black are usually available from stock.

Models available upon request

Models with 0.5 to 7 mm collet chuck (FSE...P series)

- Models with 0.5 to 10 mm collet chuck (FDE...P series)
- Models with 0.5 to 10 mm collet chuck (FY...P series)
- Models with 3÷13 mm capacity keyed chuck (only for FO...P series: use morse taper socket code 407012040 and keyed chuck code 650090160)
- Models predisposed for conveying air exhaust
- In special manual drilling situations and drilling-equipment mounted applications, Fiam manufactures special drills, in a very wide range of speeds, with direct air inlet for remote control use, and with smooth or flanged housings. Given the wide variety of solutions possible, Fiam's qualified Technical Consultancy Service is at your disposal for any further information

Standard equipment (supplied with the tool)

- Drills with self-locking chuck: self-locking chuck Drills with keyed chuck: keyed chuck and key
- Hanging ring
- Auxiliary grip (prEN792 1-12 standard)
 Use and maintenance manual Eco-friendly packaging

Accessories available upon request

• Wide range of accessories for air drills and the compressed air system (see page 18-23).

Other technical features

	/ / /		/Supply hoses recommended*				
Models	Air inlet	Recommended hose bore	Rubber	Spiral			
FSEP, FDEP, FYP	1/4" gas	Ø 8 mm	693511022	693011020			
FOP	3/8" gas	Ø 13 mm	693511023	-			

^{*} For features of hoses see p. 20

The data given in the table are indicative and can be changed without

The data given in the table are indicative and can be changed without prior notice. The values indicated for noise levels were obtained in the laboratory, performing tests that comply with the standards stated, but alone are not sufficient for calculating risks. Values measured in the single work places may be higher than those stated. The values of actual exposure and consequent risks are specific and depend on the operator's method of work, the type of work piece and the work

place, as well as the operator's time of exposure and his physical

Conductions.

Fiam cannot be held responsible for any consequences deriving from the use of the information in the table when evaluating risks in the work place over which Fiam has no control. For all further details, please apply to the FiamTechnical Consultancy Service.

Angle air drills FZ, FS, FY

Angle air drills

IDLE SPEED:

from 500 to 4.500 r.p.m.

DRILLING CAPACITY:

from 1 to 10 mm Ø

TYPE OF DRILL:

- with self-locking chuck
- with keyed chuck
- without chuck

Models with 30° (FZ series) and 90° angle heads 90° angle drills (FS series) are also available in the version which permits the use of collet instead of the normal keyed chuck



STARTING SYSTEM:

lever

APPLICATION FIELD:

they are necessary when one needs to drill in tight spaces where access is difficult, such as up against walls, close to metal sections and profiles beams



Angle air drills FZ, FS, FY

						_	_					
Tho or on		Qu.	The of chick strolley	Chuck capacity	plays maling	, /Dagogs app	Stating Systes	Weight	Dinersións (mm)	of Constant	Moise level	Vilorazions (evegions
Model	Code	Туре	Туре	mm	Туре	r.p.m.	Туре	Kg	ØxL xH	l/s	dBA	m/s²
FZ31/30P	122335132	~~	Collet chuck	1÷5	-	3100		0,500	31x235x35	6	76	< 2,5
FZ31/90P	122395132		Collet chuck	1÷5	-	3100	-	0,500	31x228x47	6	76	< 2,5
FS65/90A	124609091		Self-locking chuck	0÷6	_	4500		1,250	40x255x100	9	76	< 2,5
FS65/90C	124691118		Keyed chuck	0÷6	-	4500		1,100	40x255x83	9	76	< 2,5
FS65/90P	124695104		Collet chuck	1÷7	-	4500		1,000	40x255x54	9	76	< 2,5
FS65/90	124609093		Without chuck	0÷6*	1	4500	-	0,970	40x255x54	9	76	< 2,5
FS48/90A	124609212		Self-locking chuck	0÷6	_	3400	-	1,250	40x255x100	9	76	< 2,5
FS48/90C	124691116		Keyed chuck	0÷6	-	3400		1,100	40x255x83	9	76	< 2,5
FS48/90P	124695106		Collet chuck	1÷7	-	3400	-	1,000	40x255x54	9	76	< 2,5
FS48/90	124609155		Without chuck	0÷6*	1	3400		0,970	40x255x54	9	76	< 2,5
FS33/90A	124609124	1	Self-locking chuck	0÷8	-	2200		1,250	40x255x100	9	76	< 2,5
FS33/90C	124691108		Keyed chuck	0÷8	-	2200		1,100	40x255x83	9	76	< 2,5
FS33/90P	124695108		Collet chuck	1÷7	_	2200	-	1,000	40×255×54	9	76	< 2,5
FS33/90	124609154	1	Without chuck	0÷8*	1	2200		0,970	40x255x54	9	76	< 2,5
FS17/90A	124609083	1	Self-locking chuck	1÷10	_	1100		1,420	40x285x112	9	76	< 2,5
FS17/90C	124691112		Keyed chuck	1÷10	-	1100		1,300	40x285x90	9	76	< 2,5
FS17/90P	124695112		Collet chuck	1÷7	-	1100		1,200	40x285x54	9	76	< 2,5
FS17/90	124609211	1	Without chuck	1÷10*	1	1100		1,070	40x285x54	9	76	< 2,5
FS10/90A	124609210	1	Self-locking chuck	1÷10	-	700		1,420	40x285x112	9	76	< 2,5
FS10/90C	124691114		Keyed chuck	1÷10	-	700		1,300	40x285x90	9	76	< 2,5
FS10/90P	124695114		Collet chuck	1÷7	-	700		1,200	40x285x54	9	76	< 2,5
FS10/90	124609075	_	Without chuck	1÷10*	1	700		1,070	40x285x54	9	76	< 2,5
FY8/90A	126309060	1	Self-locking chuck	1÷10	_	1600		1,820	46x320x125	10	80	< 2,5
FY8/90C	126391101		Keyed chuck	1÷10	-	1600		1,700	46x320x103	10	80	< 2,5
FY8/90	126309062	1	Without chuck	1÷10*	2	1600		1,480	46x320x65	10	80	< 2,5
FY10/90A	126309104	_	Self-locking chuck	1÷10	-	1200		1,820	46x320x125	10	80	< 2,5
FY10/90C	126391102		Keyed chuck	1÷10	_	1200		1,700	46x320x103	10	80	< 2,5
FY10/90	126309064		Without chuck	1÷10*	2	1200		1,480	46x320x65	10	80	< 2,5
FY13/90A	126309071		Self-locking chuck	1÷10	_	500	-	2,020	46x350x125	10	80	< 2,5
FY13/90C	126391103		Keyed chuck	1÷10	-	500		1,900	46x350x103	10	80	< 2,5
FY13/90	126309082		Without chuck	1÷10*	2	500		1,680	46x350x65	10	80	< 2,5

FZ, FS, FY...A = models with self-locking chuck • FZ, FS, FY...C = models with keyed chuck • FZ, FS, FY...P = models with collet chuck • FZ, FS, FY... = models without chuck. • For the right choice, see page 3.

(a) OUTPUT SHAFT

1 - Threaded 3/8" x 24 UNF. • 2 - Threaded 1/2" x 20 UNF.

* Chuck capacity
The indicated capacity is the maximum recommended.



- To choose the right air drill, it is necessary to check
- the drilling capacity in the chart on page 3.

 The figures shown are measured at a pressure of 6,3 bar (ISO 2787), the recommended operating pressure.

 Noise level has been measured in accordance with ISO 3744 and ISO 15744.
- Vibrations level has been measured in accordance with ISO 8662
- The code number must be used when ordering.

The models highlighted in black are usually available from stock.

The data given in the table are indicative and can be changed without prior notice. The values indicated for noise levels were obtained in the laboratory, performing tests that comply with the standards stated, laboratory, performing tests that comply with the standards stated, but alone are not sufficient for calculating risks. Values measured in the single work places may be higher than those stated. The values of actual exposure and consequent risks are specific and depend on the operator's method of work, the type of work piece and the work place, as well as the operator's time of exposure and his physical conditions.

Fiam cannot be held responsible for any consequences deriving from the use of the information in the table when evaluating risks in the work place over which Fiam has no control. For all further details, please apply to the FiamTechnical Consultancy Service.

Standard equipment (supplied with the tool)

- Drills with self-locking chuck: self-locking chuck
- Drills with keyed chuck: keyed chuck and key
- Drills with collet chuck: locking key for socket (the collet has to be ordered apart, see page 19)
- Use and maintenance manual
- Eco-friendly packaging

Accessories available upon request

• Wide range of accessories for air drills and the compressed air system (see page 18-23)

Models available upon request

- · Models with customized output shaft (only for models FS.../90... and FY.../90...)
- In special manual drilling situations and drillingequipment mounted applications, Fiam manufactures special drills, in a very wide range of speeds, with direct air inlet for remote control use, and with smooth or flanged housings. Given the wide variety of solutions possible. Fiam's qualified Technical Consultancy Service is at your disposal for any further information.

Other technical features

/	/ / /		/Supply hoses recommended*			
Models	Air inlet	Recommended hose bore	Rubber	Spiral		
FZ/30, FZ/90	1/8" gas	Ø 5 mm	693511020	-		
FS/90, FY/90	1/4" gas	Ø 8 mm	693511022	693011020		

*For features of hoses see p. 20

DIMENSIONS (mm)

