

Grinders

Straight models



Type	Brand	Wheel size mm	RPM	Power kW	Spindle	Air cons. l/s	Weight kg	Inlet-thread	Hose diameter mm	Vibration m/s²	Noise level dB(A)
GS-2EFS*	YOKOTA	65 x 13 x 9,5	14.000	0,45	3/8" x 16	10,0	1,3	PT 1/4"	10	3	84
TSG-3L	TOKU	75 x 13 x 9,5	11.500	0,53	3/8"	8,3	1,6	PT 3/8"	10	0,8	73
TSG-4L	TOKU	100 x 19 x 15,9	9.000	1,05	5/8"	16,6	3,0	PT 3/8"	13	1,1	83
TSG-5L	TOKU	125 x 19 x 12,7	7.600	1,05	1/2"	16,6	3,0	PT 3/8"	13	1,5	79
TSG-6L	TOKU	150 x 25 x 15,9	6.000	1,58	5/8"	20,0	4,2	PT 3/8"	13	0,8	80

*silenced

Vertical grinders



Type	Brand	Wheel size mm	RPM	Power kW	Spindle	Air cons. l/s	Weight kg	Inlet-thread	Hose diameter mm	Vibration m/s²	Noise level dB(A)
7VC-6500FS*	YOKOTA	230 x 6 x 22	6.500	1,74	5/8"	23,0	4,2	PT 3/8"	13	3	82
7VC-8500FS*	YOKOTA	180 x 6 x 22	8.500	1,74	5/8"	23,0	4,1	PT 3/8"	13	2,1	83

*silenced

All vertical and straight grinders have a governor wheel for regulating the right speed of the grinding wheel. This reduces the risk of overspeeding and assures the best material removal.

Both Yokota and Toku straight grinders have double rows of bearings for long lifetime.

Grinders

Angle models



Type	Brand	Wheel size mm	RPM	Power kW	Spindle (Whitworth) mm	Air cons. l/s	Weight kg	Inlet-thread	Hose diameter mm	Vibration m/s²	Noise level dB(A)
RRG-1040AL	RRA	100 x 1 x 9,6	14.000	0,76	M6	11,0	1,7	PT 1/4"	10	2,5	83
G-40SRF	YOKOTA	100 x 6 x 16	13.000	0,39	M8 x 1,25	7,5	0,90	PT 1/4"	10	6,6	79
RRG-2034*	RRA	100 x 6 x 16	10.000	0,45	M10	11,0	1,55	PT 1/4"	10	2,3	83
TAG-40FLH*	TOKU	100 x 6 x 16	13.000	0,55	M8	10,8	1,70	PT 3/8"	10	2,6	83
RRG-2044*	RRA	115 x 6 x 22	10.000	0,45	M14x2	11,0	1,60	PT 1/4"	10	2,4	83
G-40EF*	YOKOTA	115 x 6 x 22	13.000	0,60	7/16"	10,8	1,40	PT 1/4"	10	6,6	79
TAG-45MLH*	TOKU	115 x 6 x 22	13.000	0,67	M14x2	10,8	1,80	PT 3/8"	10	2,7	83
RRG-2055*	RRA	125 x 6 x 22	10.000	0,45	M14x2	11,0	1,60	PT 1/4"	10	2,4	83
G-50EF*	YOKOTA	125 x 6 x 22	12.000	0,60	7/16"	10,8	1,50	PT 1/4"	10	4	77
G-50RF*	YOKOTA	125 x 6 x 22	12.000	0,60	7/16"	10,8	1,40	PT 1/4"	10	4	77
TAG-50MLH*	TOKU	125 x 6 x 22	12.000	0,67	M14x2	10,8	1,80	PT 3/8"	10	2,7	83
RRI-G50*	RRI	125 x 6 x 22	12.000	1,25	M14x2	22	1,8	PT 1/4"	13	<2,5	83
RRI-GT50F*	RRI	125 x 6 x 22	12.200	2,2	M14x2	30	1,8	PT 1/2"	13	<2,5	79
G-70EF*	YOKOTA	180 x 6 x 22	8.500	1,12	5/8"	16,7	2,90	PT 3/8"	13	2,3	82
TAG-700QJL*	TOKU	180 x 6 x 22	8.500	1,10	-	16,6	3,10	PT 3/8"	13	2,6	82
TAG-900QJL*	TOKU	230 x 6 x 22	6.500	1,10	-	16,6	3,10	PT 3/8"	13	3,6	82

* Vibration reduced side-handle.

All angle grinders are supplied with regulator (for optimal safety and the correct RPM for best material removal).

RRG-2034, RRR-2044 and RRG-2055 are supplied with flanges for wheel thickness of 0,8 - 6 mm.

Flanges for cup wheels and a tool service set for mounting the flanges are supplied with all grinders.

TAG-45MLH and TAG-50MLH are supplied with flanges for wheel thickness of 1,6 - 6 mm and have a spindle lock.

All angle grinders are supplied with an vibration reduced side handle, with exception of the models HS-4G and G-40SRF.

For model G-70EF, flanges for flat wheels have to be ordered seperately.